



Luxpower series 5

530-550 W Mono

M 10/182 mm Cell. 144 Half-Cell Layout

- Gallium-doped Technology
- Half Cut Cell Technology
- MBB Technology
- Anti-PID -Low LID- Performance
- Less Hot Spot Shading Effects
- Lower BOS & LCOE
- 12- Year Product Warranty
- 25- Years PowerWarranty

MECHANICAL CHARACTERISTICS

Solar Cells	Mono
No.of Cell	144 (6x24)
Dimension	2279 x 1134 x 35mm
Weight	27.5kg
Front Glass	3.2 mm coated tempered glass
Frame	Anodized Aluminium alloy
Junction Box	Ip68, rated (3 pass diodes)
Output Cable	4.0 mm ² , 300mm (+) 400 mm (-) Length can be customized
Connectors	Mc4 compatible
Mechanical load test	5400Pa

ELECTRICAL PARAMETERS

Power Class	LNVU-530M		LNVU-535M		LNVU-540M		LNVU-545M		LNVU-550M	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	530W	401W	535W	405W	540W	409W	545W	413W	550W	417W
Open Circuit Voltage (Voc)	49.74V	47.16V	49.89V	47.40V	50.04V	47.63V	50.18V	47.87V	50.32V	48.10V
Short Circuit Current (Isc)	13.62A	10.91A	13.69A	10.95A	13.76A	10.99A	13.83A	11.03A	13.90A	11.07A
Voltage at Maximum Power (Vmpp)	41.63V	38.97V	41.80V	39.21V	41.96V	39.44V	42.12V	39.67V	42.28V	39.90V
Current at Maximum Power (Impp)	12.73A	10.29A	12.80A	10.33A	12.87A	10.37A	12.94A	10.41A	13.01A	10.45A
Module Efficiency (%)	20.51%		20.70%		20.89%		21.09%		21.28%	

OPERATING PARAMETERS

Operational Temperature	-40°C ~ +85°C
Maximum System Voltage	1500 DC (IEC)
Maximum Series Fuse Rating	25A
Power Tolerance	0/+5W
Nominal Operating Temperature	45±2°C
Temperature coefficient of Voc	-0.36%/°C
Temperature coefficient of Pmax	-0.28%/°C
Temperature coefficient of Isc	+0.05%/°C

STC: Irradiance 1000W/m², cell temperature 25°C, AM1.5G NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s, AM1.5G